

1-888-726-9752

SEISCO ELECTRIC TANKLESS WATER HEATERS & APPLICATIONS

SEISCO'S PATENTED CONTROL SYSTEM (1) PROVIDES FOR EFFICIENCY AND CONTINUOUS, ENDLESS HOT WATER AND (2) USES VARIABLE ENERGY INPUT SO THAT THE ONLY THE ENERGY REQUIRED TO HEAT THE WATER TO THE DESIRED TEMPERATURE IS USED.

THE SEISCO WATER HEATER IS A TANKLESS WHOLE-HOUSE (RA-22 & RA-28) WATER HEATER. THE USE OF ENGINEERING COMPOSITE MATERIALS PREVENTS RUST & VIRTUALLY ELIMINATES CORROSION TO THE CHAMBER. THESE FEATURES ENABLE THE COMPANY TO PROVIDE A LIMITED 10-YEAR WARRANTY ON PLASTIC CHAMBER AND CIRCUIT BOARD.

SERVICE LOAD CALCULATIONS SHOULD ALWAYS BE PERFORMED TO INSURE COMPLIANCE WIT THE CURRENT NATIONAL ELECTRIC CODE, AND ANY APPLICABLE LOCAL PLUMBING. ELECTRICAL, HEATING AND AIR CONDITIONING CODES. ALL UNITS REQUIRE 240 VOLTS A.C. GROUND NEUTRAL.

28 kw

95 DEGREE TEMPERATURE RISE AT 2.0 GALLONS PER MINUTE.

EXCELLENT RESIDENTIAL UNIT. EXCELLENT CHOICE FOR COMMERCIAL USE IN:
SPECIALTY RESTAURANTS, CONVENIENCE STORES, HOTELS, PET GROOMING ESTABLISHMENTS.

EXCELLENT BACK-UP TO PASSIVE SYSTEMS SUCH AS SOLAR AND HEAT RECOVERY
MAX AMPS - 116; BTU RATING -95564, BREAKERS - 4 @ 30 AMP

22 kw

75 DEGREE TEMPERATURE RISE AT 2.0 GALLONS PER MINUTE. FOR USE WHERE AMBIENT WATER TEMPERATURE RARELY DROPS BELOW 60 DEGREES.

MAX AMPS - 91 ; BTU RATING - 75086; BREAKERS - 2 @ 50 AMP

14 kw

64 DEGREE TEMPERATURE RISE AT 1.5 GALLONS PER MINUTE .

EXCELLENT CHOICE FOR:
SINGLE SHOWER/SINK APPLICATIONS, HUNTING OR FISHING CABINS, SUPPLEMENTING EXISTING WATER HEATERS WHICH ARE UNABLE TO SATISFY USERS REQUIREMENTS

MAX AMPS-58; BTU RATING - 47792; BREAKERS-2 @ 30 AMP

11 kw

50 DEGRE TEMPERATURE RISE AT 1.5 GALLONS PER MINUTE

EXCELLENT CHOICE FOR POINT OF USE APPLICATIONS
COFFEE BARS, WASH SINKS IN LIGHT INDUSTRIAL OFFICE WAREHOUSE, EMERGENCY SHOWERS, MULTIPLE BATHROOM SINKS TO COMPLY WITH CODE, AND SUPPLEMENTING EXISTING WATER HEATERS

MAX AMPS - 46 BTU RATING - 7543 ; BREAKERS - I @ 50 AMP